

Aalto Ultra Premium Interior Low Sheen

A beautiful eggshell finish, perfect for living area walls

Aalto Ultra Premium Interior Low Sheen is a premium waterbased paint in a low sheen finish for interior walls and ceilings. This reinforced acrylic paint has been formulated to provide a beautiful matt appearance while delivering a washable finish with excellent stain resistant properties.

Product Aalto Ultra Premium Interior Low Sheen AA332

Guarantee Aalto Ultra Premium Interior Low Sheen comes with a 15 year guarantee. For details, visit www.aalto.co.nz

Typical Uses May be used on suitably prepared:

- Plasterboard, wallboard, Gib® board
- Timber
- Fibrous plaster
- Customwood

Physical Properties

Binder type	Reinforced acrylic
Solvent	Water
Colour	White and tinted colours
Finish	Low sheen / 5% gloss
Dry time	1 hour at 20°C
Recoat time	2 hours at 20°C
Number of coats	2
Theoretical coverage	10-12m ² per litre
Recommended film thickness	100 microns per coat, WFT
Thinning and clean up	Water

Preparation Ensure surfaces are free from loose and flaking paint. Wash surfaces with a suitable cleaner such as sugar soap prior to painting to remove dirt, oils, grease and other contaminants. Where there has been mould, treat the area with a moss and mould remover.

Stir well before and during use with a broad, flat paddle, using an up and down scooping motion.

Application Aalto Ultra Premium Interior Low Sheen can be applied by synthetic brush, roller, or spray.

- Airless spray – a 415 or 515 tip is recommended
 - When spraying, Aalto Ultra Premium Interior Low Sheen may require thinning to suit
- Rolling – a 10mm microfibre or dacron roller sleeve is recommended

New plasterboard, wallboard, Gib® board

1. Apply 1 coat of Aalto Tradeline Interior Sealer Undercoat
2. Apply 2 coats of Aalto Ultra Premium Interior Low Sheen, allowing 2 hours between coats



Timber, fibrolite, HardieFlex™, customwood

1. Apply 1 coat of Aalto Ultra Premium 3 in 1 Undercoat
2. Apply 2 coats of Aalto Ultra Premium Interior Low Sheen, allowing 2 hours between coats

Repaints

1. Spot prime if/where required with Aalto Ultra Premium 3 in 1 Undercoat
2. Apply 2 coats of Aalto Ultra Premium Interior Low Sheen, allowing 2 hours between coats

Maintenance

Maintain your interior paint finish by cleaning with a damp cloth and neutral detergent (such as diluted sugar soap). Cleaners that contain solvents may affect the surface appearance and the paint's longevity. Dry dust corners frequently to avoid dust and dirt build up.

Performance and Limitations

Performance

- Excellent washability
- Exceptional coverage and opacity
- Easy to apply
- Excellent stain resistance
- Low odour, low VOC

Limitations

- Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period
- Dry time may be impeded if the relative humidity is high
- Should not be used on closing surfaces of doors or window frames, or on areas subject to pressure
- Full stain resistance may take up to 7 days to develop

Health and Safety

For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.

aalto

Disclaimer

Copyright Aalto Group Ltd. 2024

Any information provided in this data sheet is provided in good faith and is correct at the time of publication. Application details are based on generic scenarios, for any specific application details please contact your Aalto paint specialist.

Products and coating systems can be expected to perform as stated in this data sheet, provided the substrate is in good condition, preparation is completed to a high standard, and application is carried out by a suitably experienced/skilled applicator.

aalto