

Procoat Fence Paint

Product	Procoat Fence Paint PR434	
Description	Procoat Fence Paint is a solid colour waterbased paint that provides an even, low sheen finish. Formulated for NZ conditions, it has easy application properties, is low odour, and fast drying. Ideal for use on timber fences and trellis, including rough sawn timber fences, and fences previously painted with acrylic paint.	
Typical Uses	May be used on suitably prepared: <ul style="list-style-type: none"> - Bare, rough sawn timber fences - Post and rail fences - Fences previously painted with acrylic paint 	
Physical Properties	Binder type	100% acrylic
	Solvent	Water
	Colour	Range of standard colours
	Finish	Low sheen
	Dry time	40 minutes at 20°C
	Recoat time	2-4 hours at 20°C
	Number of coats	2
	Theoretical coverage	6-10m ² per litre per coat
	Thinning and clean up	Water
Preparation	<p>Ensure the surface is dry, free from dirt, dust and other contaminants. Wash surfaces with Procoat Exterior House & Deck Wash prior to painting. Treat any moss or mould present.</p> <p>Stir well before and during use with a broad flat paddle, using an up and down scooping motion.</p> <p>Note: Bare timber must be adequately dry before painting. Wet timber will decrease penetration and adhesion, and decrease the life of the coating. New LOSP treated timber should be left for 14 days before painting.</p>	
Application	<p>Procoat Fence Paint may be applied by synthetic brush, roller, or spray. Consult your local paint specialist for recommendations.</p> <ol style="list-style-type: none"> 1. Stir well before and during use 2. Apply 2 coats Procoat Fence Paint, allowing 2-4 hours between coats 	
Performance and Limitations	Performance	<ul style="list-style-type: none"> - Great durability on suitably prepared timber - Easy to apply
	Limitations	<ul style="list-style-type: none"> - Should not be applied if temperatures are below 10°C or when it is liable to drop below 10°C during the drying period - Coverage may be reduced on previously painted surfaces



Health and Safety For detailed health and safety information refer to Material Safety Datasheet (MSDS)

Usage

- Provide adequate ventilation during use
- Keep out of reach of children

Personal

- Avoid contact with skin and eyes
- Wash hands after use

Protective equipment

- Wear protective eyewear and waterproof gloves
- When spraying, wear dust mask or suitable respirator

Storage

- Store away from direct sunlight

Health Effects

If poisoning occurs, contact a doctor or Poisons Information Centre (NZ 0800 764 766).

If swallowed: Rinse mouth with water. Do NOT induce vomiting. Give a glass of water.

Eyes: If in eyes, hold eyes open, flush with running water for at least 15 minutes,

Skin: If skin contact occurs, remove contaminated clothing and wash skin thoroughly.

Inhaled: Remove from contaminated area.

Spills and Disposal

Do not allow spilt material to enter drains or other watercourses. Absorb spills with sand or other inert material. Do not pour leftover paint down the drain. Unwanted paint should be kept in a sealed container, such as an empty paint can, and disposed of via special waste collection services. Check with your local council regarding the disposal of empty paint containers. Empty paint containers should be left open in a well-ventilated area to dry out. When dry, recycle steel containers via steel can recycling programs. Disposal of empty paint containers via domestic recycling programs may vary between local authorities.